

REMARKS

The claims now pending in the application are Claims 1 to 24, 30 to 32 and 34 to 36, the independent claims being Claims 1, 8, 15, 30 to 32 and 34 to 36. Claims 25 to 29, 33 and 37 have been cancelled herein. Claims 1 to 24, 30 to 32 and 34 to 36 have been amended herein.

In the Official Action dated February 5, 2004, Claims 1 to 37 were rejected under 35 U.S.C. § 102(e), as anticipated by U.S. Patent No. 6,680,746 (Kawai). Reconsideration and withdrawal of the rejection respectfully are requested in view of the above amendments and the following remarks.

The rejections of the claims over the cited art respectfully are traversed. Nevertheless, without conceding the propriety of the rejections, Claims 25 to 29, 33 and 37 have been cancelled and Claims 1 to 24, 30 to 32 and 34 to 36 have been amended herein more clearly to recite various novel features of the present invention, with particular attention to the Examiner's comments. Support for the proposed amendments may be found in the original application. No new matter has been added.

The present invention relates to a novel communication system. In one aspect, as now recited in independent Claim 1, the present invention relates to a communication apparatus which is connected to at least one camera and at least one monitor and manages information concerning a state of the at least one camera. The communication apparatus comprises a reception device that receives the information concerning the state of the at least one camera, and a transmission device that transmits the information concerning the state of the at least one camera received by the receiving device to the at least one monitor, so as to change a display concerning the state of the at least one camera displayed on the at least one monitor; in this aspect, when the state of any one of the at least one camera is changed, the transmission device transmits the information concerning the changed state of that camera to the at least one monitor via a network.

In a similar aspect, as now recited in independent Claim 8, the present invention relates to such a communication apparatus including a reception device and a transmission device, wherein, when a request (i.e., for update information) from the at least one monitor is received, the transmission device transmits the information to the at least one monitor via the network.

In another aspect, as now recited in independent Claim 15, the present invention relates to a communication apparatus which is connected to at least one camera and at least one monitor and manages information concerning a state of the at least one camera. The communication apparatus comprises a reception device that receives the information concerning the state of the at least one camera, a processing device that changes a display image concerning the state of the at least one camera displayed on the at least one monitor, in accordance with the received information concerning the state of the at least one camera, and a transmission device that transmits the display image concerning the state of the at least one camera processed by the processing device to the at least one monitor via a network.

Independent Claims 30 to 32 and 34 to 36 respectively recite similar features with respect to a communication method and a communication medium which stores a computer-readable program of a control method for a communication apparatus which is connected to at least one camera and at least one monitor and manages information concerning a state of the at least one camera.

With respect to independent Claims 1, 30 and 34, in each aspect, when the state of any one of the at least one camera is changed, the transmission device (or step) transmits the information concerning the changed state of that camera to the at least one monitor connected via a network.

With respect to independent Claims 8, 31 and 35, in each aspect, when a request (i.e., for update information) is received from a monitor, the transmission device (or step) transmits the information to the (at least one) monitor connected via the network.

Applicants submit that the prior art fails to anticipate the present invention. Moreover, Applicants submit that there are differences between the subject matter sought to be patented and the prior art, such that the subject matter taken as a whole would not have been obvious to one of ordinary skill in the art at the time the invention was made.

The Kawai '746 patent relates to an apparatus and method for controlling a configuration of a video camera, and discloses a camera control system for displaying a video image input from a plurality of cameras, and for preparing a map showing icons indicating the positions of the cameras on the map, so that the direction of the cameras can be identified on the map. However, Applicants submit that the Kawai '746 patent fails to disclose or suggest at least the above-described features of the present invention. Rather, the Kawai '746 patent discloses that, in a camera operation unit 20, the received information concerning the state of the at least one camera is transmitted to a bit-map display 28 provided in the camera operation unit 20 itself. In one aspect, as described above, the present invention transmits the entire information concerning the state of (each of) the at least one camera to (each of) the at least one monitor connected via the network. As discussed in greater detail in the present application, this aspect of the present invention provides a significant improvement over systems of the prior art, in that it provides a dynamic mapping of all cameras, as well as the overall status of each camera (including direction of video taking), to all monitors connected via the network. The Kawai '746 patent is silent with respect to any operation that information is transmitted to such monitors when the state of a camera is changed, or when a request for updated information is received from each monitor, as disclosed and claimed in the present application. Further, nowhere does the Kawai '746 patent disclose or suggest an operation in which the

display image itself is transmitted to each of the at least one monitor, as disclosed and claimed in the present application.


For the above reasons, Applicants submit that independent Claims 1, 8, 15, 30 to 32 and 34 to 36 are allowable over the cited art.

Claims 2 to 7 to 9 to 14 and 16 to 24 depend from Claims 1, 8 and 15, respectively, and are believed allowable for the same reasons. Moreover, each of these dependent claims recites additional features in combination with the features of its respective base claim, and is believed allowable in its own right. Individual consideration of the dependent claims respectfully is requested.

In formal matters, submitted herewith is a substitute specification, together with a marked-up version showing amendments to correct matters of form, including English spelling, grammar, idiom, syntax and the like. No new matter has been added.

Applicants believe that the present Amendment is responsive to each of the points raised by the Examiner in the Official Action, and submit that the application is in allowable form. Favorable consideration of the claims and passage to issue of the present application at the Examiner's earliest convenience earnestly are solicited.

Applicants' undersigned attorney may be reached in our Washington, D.C. office by telephone at (202) 530-1010. All correspondence should continue to be directed to our below listed address.

Respectfully submitted,


Attorney for Applicants
Registration No. 32,078

FITZPATRICK, CELLA, HARPER & SCINTO
30 Rockefeller Plaza
New York, New York 10112-3801
Facsimile: (212) 218-2200
CPW\gmc

DC_MAIN 165142v1



03500.014173

RECEIVED

MAY 14 2004

Technology Center 2600

- 1 -

TITLE

COMMUNICATION APPARATUS, STORAGE MEDIUM, CAMERA AND PROCESSING METHOD

5

(Substitute Specification for Appln. No. 09/480,861 - Marked up Version)

BACKGROUND OF THE INVENTION

10

Field of the Invention

The present invention relates to a communication apparatus, a storage medium, a camera and a processing method.

15

Related Background Art

A ~~One~~ video transmission system has been proposed in which. ~~In this~~ system, for example, plural video cameras and computers are located inside a building, and these video cameras and the computers are networked through communication lines, thereby realizing video transmission among plural desired points and interactive communication by video and audio.

20

In ~~this~~ ~~such the~~ video transmission system, a user of the computer at one point (local computer) can remote-control the video camera at ~~a the~~ desired remote point and display the video taken by the remote-controlled video camera on the screen of the user's local own computer.

5 Further, in ~~a the~~ video transmission system capable of remote-controlling a remote the video camera, especially, as the number of the video cameras to be remote-controlled increases, it is necessary for the user to easily understand where each video camera is located. Thus, ~~a the~~ technique which superimposes a camera symbol representing the location of each video camera on an image representing a
10 map has been proposed. Further, ~~a the~~ technique which represents the direction of picture taking of the actual video camera by displaying the direction/orientation ~~direction~~ of the camera symbol has been proposed.

In the above system, there is a case where ~~a the~~ video camera which is represented by ~~a the~~ camera symbol superimposed on the map is operated and
15 controlled by a user at a remote location. In this case, as long as the terminal which utilizes that map does not obtain ~~a the~~ state update of the video camera concerned, ~~a the~~ problem exists in that the state of the camera symbol does is not correspond ~~corresponding~~ to the state of the actual video camera ~~is caused~~.

20 SUMMARY OF THE INVENTION

An object of the present invention is to provide a communication apparatus, a storage medium, a camera and a processing method which can unitarily control information concerning video cameras and transmit such ~~the~~ information to all terminals operating the video cameras.

As one preferred example of the present invention, there is provided a communication apparatus which is connected to at least one camera and at least one monitor and manages information concerning a state of the at least one camera, comprising:

5 reception means for receiving the information concerning the state of the at least one camera; and

transmission means for transmitting the information concerning the state of the at least one camera received by the reception means to the at least one monitor, so as to change a display concerning the state of the at least one camera
10 displayed on the at least one monitor,

wherein the transmission means transmits the information in correspondence with the change of the state of the at least one camera.

Another object of the present invention is to provide a communication apparatus, a communication method, a camera and a processing method each of
15 which has a new function.

Other objects and features of the present invention will become apparent from the following detailed description and the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1 is a block diagram showing the overall entire structure of a communication system including a video communication system according to one embodiment of the present invention;

Fig. 2 is a block diagram showing the structure of main software of a video transmitter 20 and a monitor 60 according to one embodiment of the present invention;

Fig. 3 is a view showing a display example of the monitor according to one embodiment of the present invention;

Fig. 4 is a view showing a display example of the monitor according to one embodiment of the present invention;

Fig. 5 is a view showing a display example of a window for displaying video from a video camera, according to one embodiment of the present invention;

Fig. 6 is a view showing the state when display is performed by a drag-and-drop operation, according to one embodiment of the present invention;

Fig. 7 is a view showing a mouse cursor of a video camera used in the drag-and-drop operation according to one embodiment of the present invention;

Fig. 8 is a view showing the state when a display area by the drag-and-drop operation is changed, according to one embodiment of the present invention;

Fig. 9 is a view showing a camera icon representing that taken video is being displayed, according to one embodiment of the present invention;

Fig. 10 is a view showing the state of an operation to stop ~~a~~ the display by the drag-and-drop operation according to one embodiment of the present invention;

Fig. 11 is a view showing a display example of the monitor according to one embodiment (fourth embodiment) of the present invention;

Fig. 12 is a flow chart showing an operation of map management software according to one embodiment (first embodiment) of the present invention;

Fig. 13 is a flow chart showing the operation of map management software according to one embodiment (first embodiment) of the present invention;

Fig. 14 is a flow chart showing an operation of video reception software according to one embodiment (first embodiment) of the present invention;

5 Fig. 15 is a flow chart showing the operation of video reception software according to one embodiment (first embodiment) of the present invention;

Fig. 16 is a flow chart showing the operation of video reception software according to one embodiment (first embodiment) of the present invention;

Fig. 17 is a flow chart showing the operation of video reception software
10 according to one embodiment (first embodiment) of the present invention;

Fig. 18 is a flow chart showing the operation of video reception software according to one embodiment (first embodiment) of the present invention;

Fig. 19 is a flow chart showing the operation of video reception software according to one embodiment (first embodiment) of the present invention;

15 Fig. 20 is a flow chart showing the operation of video reception software according to one embodiment (first embodiment) of the present invention;

Fig. 21 is a flow chart showing an operation of camera control client software according to one embodiment (first embodiment) of the present invention;

Fig. 22 is a flow chart showing the operation of camera control client
20 software according to one embodiment (first embodiment) of the present invention;

Fig. 23 is a flow chart showing an operation of video transmission software according to one embodiment (first embodiment) of the present invention;

Fig. 24 is a flow chart showing an operation of camera control server software according to one embodiment (first embodiment) of the present invention;

Fig. 25 is a flow chart showing the operation of camera control server software according to one embodiment (first embodiment) of the present invention;

Fig. 26 is a flow chart showing an operation of a map management server software according to one embodiment (first embodiment) of the present invention;

5 Fig. 27 is a flow chart showing the operation of the map management server software according to one embodiment (first embodiment) of the present invention;

Fig. 28 is a flow chart showing an operation of map management server software according to one embodiment (second embodiment) of the present
10 invention;

Fig. 29 is a flow chart showing the operation of map management server software according to one embodiment (second embodiment) of the present invention;

Fig. 30 is a flow chart showing an operation of video reception software
15 according to one embodiment (third embodiment) of the present invention;

Fig. 31 is a flow chart showing an operation of a map management server software according to one embodiment (third embodiment) of the present invention;

Fig. 32 is a flow chart showing the operation of the map management
20 server software according to one embodiment (third embodiment) of the present invention;

Fig. 33 is a flow chart showing an operation of map management software according to one embodiment (fourth embodiment) of the present invention;

Fig. 34 is a flow chart showing the operation of map management software according to one embodiment (fourth embodiment) of the present invention;

Fig. 35 is a flow chart showing an operation of a map management server software according to one embodiment (fourth embodiment) of the present invention;

Fig. 36 is a flow chart showing an operation of camera control server software according to one embodiment (fifth embodiment) of the present invention;

Fig. 37 is a flow chart showing an operation of a map management server software according to one embodiment (fifth embodiment) of the present invention; and

Fig. 38 is a flow chart showing the operation of the map management server software according to one embodiment (fifth embodiment) of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[First Embodiment]

Fig. 1 is a block diagram showing the overall ~~entire~~ structure of a communication system including a video communication system according to one embodiment of the present invention.

In Fig. 1, numeral 10 denotes a video camera which generates video (or an image signal) on the basis of a taken (captured) image. Numeral 20 denotes a video transmitter such as a work station (WS), a personal computer (PC) or the like

which transmits the image signal from the video camera 10 to a monitor 60 and receives a control signal from the monitor 60 to control the video camera 10.

Numeral 60 denotes a monitor, ~~the monitor~~ such as a the WS, a the PC or the like, ~~like~~ which receives an the image signal from the video transmitter 20 and transmits
5 a the control signal to the video transmitter 20 to control the video camera 10.

Plural ~~The plural~~ video transmitters 20 and ~~the plural~~ monitors 60 can communicate with each other ~~others~~ through a network 100. Preferably, the video transmitter analog-to-digital (A/D) converts the image signal from the video camera 10 into digital image data, compresses the obtained digital image data, and
10 transmits the compressed data to the monitor 60 through the network 100.

Numeral 12 denotes a camera control circuit which controls panning, tilting, zooming, focusing and iris stopping ~~irising~~ operations in accordance with a the control signal (i.e., a control code) from the video transmitter 20. The control signal is input via from an input/output interface (I/O) 32 of the video transmitter
15 20 to the camera control circuit 12 on the basis of, e.g., an RS-232C standard or the like.

If a the video camera 10 does not perform ~~performs the~~ panning, tilting, zooming, focusing and iris stopping ~~irising~~ operations, a the camera control circuit 12 is not always necessary. However, it is preferable to control at least an ON/OFF
20 function of the power supply of the video camera 10.

(Video Transmitter 20)

Next, the structure of the video transmitter 20 will be explained. Numeral 24 denotes a main memory, and numeral 26 denotes a storage unit such as a hard disk or the like. Numeral 28 denotes a mouse which acts as a pointing device.

However, other devices such as a touch panel on a bit map display 35 and the like may be also used. Numeral 30 denotes a keyboard which acts as input means. Numeral 25 denotes an external memory from which a storage medium such as a floppy disk, a CD-ROM or the like is detachable. Numeral 32 denotes an the I/O
5 which is connected to the camera control circuit 12 to transmit and receive a the control signal of the video camera 10. Numeral 34 denotes a video capture board which captures a video output signal VD of the video camera 10. The video output signal VD may be an analog signal such as a general NTSC (National Television System Committee) signal or a digital signal. If the signal VD is an the analog
10 signal, it is necessary for the video capture board 34 to have ~~has~~ an A/D conversion function. Numeral 36 denotes a video board which obtains the video captured by the video capture board 34 through a system bus 39 and displays the obtained video at an arbitrary location on the bit map display 35. Numeral 38 denotes a network interface (I/F) which communicates with the monitor 60 through the network 100.
15 The above units are connected to each other ~~others~~ through the system bus 39, and a CPU 22 controls the video transmitter 20 as a whole and the display of the bit map display 35 in accordance with software stored in the storage medium or the storage unit 26 or software obtained through the network 100.

If the video capture board 34 does not have a data compression function,
20 it is possible to provide software for realizing such a the function, whereby the CPU 22 can perform data compression processing.

Using a ~~By such the~~ video transmitter 20 as structured above, the image data taken by the video camera 10 is transmitted to the monitor 60 at a remote

location through the network 100, and a ~~the~~ video camera 10 is controlled according to a ~~the~~ control code received from the monitor 60.

(Monitor 60)

Next, the structure of a ~~the~~ monitor 60 will be explained. It should be
5 noted that, in the monitor 60, explanation of ~~the~~ devices or ~~the~~ units which are
the same as those in the video transmitter 20 (designated by like or similar
reference numerals) will be omitted. A network I/F 138 receives ~~the~~ compressed
image data from the video transmitter 20. A CPU 122 decompresses the received
data (i.e., encoded data) by using a video compression decoder 33, and controls a
10 video board 136 on the basis of the decompressed image data to cause a bit map
display 135 to display the image taken by the video camera 10 and the state of the
video camera 10. Further, the CPU 122 transmits a ~~the~~ control code to the video
transmitter 20, 20 for controlling the video camera 10, in accordance with data
input by the user of the monitor 60 using ~~with use of~~ a keyboard 130 or a mouse
15 128.

Next, the software of the video transmitter 20 and the monitor 60
according to the present embodiment will be explained. It should be noted that the
software explained hereinafter is executed by the hardware of the video transmitter
20 or the monitor 60.

20 Fig. 2 is a block diagram showing the structure of the main software of the
video transmitter 20 and the monitor 60 according to one embodiment of the
present invention.

First, the software to be executed by the monitor 60 will be explained.
Numeral 411 denotes camera control client software which is provided to remote

control ~~a the~~ video camera 10 connected to ~~a the~~ video transmitter 20. Numeral 412 denotes video reception software which is provided to decompress ~~the~~ compressed image data transmitted from ~~a the~~ video transmitter 20 in the form of packets packet and to display the decompressed image data. Further, the video

5 reception software 412 is provided to manage image data received from all of the plural video transmitters 20 (i.e., the video cameras 10) connected to the network 100. Using ~~By~~ the video reception software 412, a camera ID of each video camera, a host computer ID of the video transmitter 20 to which the video camera concerned is connected, ~~the~~ information concerning ~~the~~ camera operation states

10 such as ~~the~~ panning, tilting, zooming, focusing and iris stopping ~~irising~~ operations, ~~the~~ information concerning whether or not the video camera concerned is controllable (accessible), ~~the~~ state information concerning which video camera is currently is being controlled, and ~~the~~ state information concerning which video camera is currently is being displayed, ~~displayed~~ are stored in into the monitor 60.

15 Also, ~~Also~~ the camera control client software 411 and map management software 413 share such ~~the~~ information, whereby the information is utilized to effect camera symbol change or the like. Numeral 413 denotes the map management software, ~~software~~ which uses a GUI (graphical user interface) function. The GUI function is provided to graphically display the location, the panning state and the

20 tilting state of ~~a the~~ video camera 10 and to control the operation of the camera 10, using ~~by~~ a map, the camera symbol and ~~a~~ later-described scope display of Fig. 6. The above software is prestored into the storage unit of the monitor 60.

Next, the software to be executed by the video transmitter 20 will be explained. Numeral 421 denotes camera control server software which is provided

to control ~~the~~ panning, tilting, zooming, focusing and iris stopping ~~irising~~ operations of ~~a the~~ video camera 10 connected to ~~a the~~ video transmitter 20, 20 and also to capture the image data output from the video camera 10 to the video transmitter 20. Numeral 422 denotes video transmission software which

5 cooperates with the camera control server software 421 and is provided to transmit the video to the monitor 60 currently controlling the video camera 10. The above software is prestored into the storage unit of the video transmitter 20.

Numeral 431 denotes map management server software which is provided to unitarily manage the states of all the video cameras of the plural video

10 transmitters 20, 20 and to update map information. It should be noted that one map management server software 431 is executed in one system. Fig. 2 shows that the map management server software 431 is executed in ~~a the~~ video transmitter 20. However, the map management server software 431 may be executed in ~~a the~~ monitor 60, 60 or in another computer connected to the network 100. In this case,

15 the network address of the computer which executes the map management server software 431 is stored in all of the monitors 60 and ~~the~~ video transmitters 20 connected via the network.

The map management server software 431 communicates with the video reception software of the monitor 60 and the camera control server software 421 of

20 the video transmitter 20, to update the map information of the system.

Needless ~~It is needless~~ to say ~~that~~, in addition to the above software, software for controlling two-way communication through the network 100, software for controlling the storage units 26 and 126, software for controlling the external memories 25 and 125, and the like are provided ~~prepared~~ in the system.

(User Interface)

Next, ~~a the~~ user interface in the present embodiment, i.e., ~~a~~ screen which is displayed on the bit map display 135, will be explained. To simplify the explanation, the user interface will be explained on the premise that one monitor
5 60 is connected to the video transmitter 20 through the network.

Figs. 3 and 4 are views showing a display example of the monitor according to one embodiment of the present invention. Concretely, Figs. 3 and 4 show one example of the screen displayed on the bit map display 135 of the monitor 60. In Fig. 3, numeral 500 denotes a map window in which the map is
10 displayed. In the present embodiment, plural maps 510, 520, 530 and 540 showing layouts of offices, establishments (or stores), warehouses and the like are managed within the map window 500. ~~Each~~ ~~Since each~~ map is provided ~~added~~ with a map tab; ~~tab~~, if the map tab is clicked by the mouse 128, the map provided ~~added~~ with the clicked tab is displayed up-front (as a map display area 502). At
15 this time, ~~the~~ camera symbols are displayed on the up-front map.

Fig. 3 shows the state that the map 520 is selected from among the maps 510 to 540 and displayed on the map display area 502. On the map 510, video camera symbols (or video camera icons) 521, 522, 523 and 524 are displayed as
icons. At this time, if the map tab of the map 530 is clicked, the map 530 will be
20 displayed, ~~is displayed~~ as shown in Fig. 4.

In Fig. 4, the map 530 is displayed on the map display area 502, and video camera symbols (or video camera icons) 531 and 532 are displayed on the map
530.

Fig. 5 is a view showing a display example of a window for displaying the video (or the image) from the video camera, according to one embodiment of the present invention. As shown in Fig. 5, in a window 600, the videos taken by the plural video cameras 10 are displayed on plural video display areas 610, 612, 614, 616, 618 and 620, 620 respectively. Numeral 632 denotes a trash can icon which is used to delete (stop) ~~the~~ displayed video from a ~~the~~ video display area. Numeral 640 denotes a video camera control panel which includes camera control buttons for the video camera 10. It is possible by handling these buttons to control the panning, tilting, zooming, focusing and iris stopping ~~irising~~ operations of the video camera 10.

In the present embodiment, ~~the~~ six areas are displayed by way of example. However, the present invention is not limited to this. Further, these areas may be commonly displayed on the same screen as ~~which is identical with~~ the window shown in Fig. 3 or 4.

Next, an outline of software operation of the video communication system according to the present embodiment (including the GUI) will be explained with reference to Figs. 6, 7, 8, 9 and 10. In the present embodiment, if a ~~the~~ camera icon on a ~~the~~ map 520, 530 or the like is dragged and dropped (i.e., a drag-and-drop operation) onto an ~~the~~ arbitrary video display area within the video display window, then ~~the~~ motion video transmitted from the ~~video camera~~ corresponding video camera (corresponding to the one dragged and dropped) ~~dropped icon~~ is displayed on the video display area onto which the camera icon is dropped.

Fig. 6 is a ~~the~~ view showing the state when the display is performed by the drag-and-drop operation, according to one embodiment of the present invention.

Concretely, Fig. 6 shows the state that video camera icon 523 is dragged and dropped onto the video display area 614. An area 580 represents a video-taking range of the camera 523. If the mouse cursor is located within in the range 580 and the range 580 is changed from the solid-line range to a dotted-line range, a camera

5 zooming operation is performed ~~changed~~, whereby the video-taking range can be changed. Similarly, ~~the~~ panning and tilting operations can be performed by managing the area 580. Fig. 7 is ~~a the~~ view showing ~~a the~~ mouse cursor of the video camera used in the drag-and-drop operation according to one embodiment of the present invention. Fig. 8 is the view showing the state when the location of a

10 display area is changed from window 614 to window 612 by the drag-and-drop operation ~~is changed~~, according to one embodiment of the present invention. Fig. 9 is ~~a the~~ view showing ~~a the~~ camera icon representing that ~~the taken~~ video is being displayed, according to one embodiment of the present invention. Fig. 10 is ~~a the~~ view showing the state of an the operation to stop the display of video in a window

15 614 by ~~a the~~ drag-and-drop operation according to one embodiment of the present invention.

In the present embodiment, during ~~a the~~ drag-and-drop operation, the shape of the mouse cursor is represented as a camera shown in Fig. 7, whereby the user can confirm that the drag-and-drop operation is being performed. At this time,

20 on the basis of the location information of the dragged camera, the map management software 413 searches for the ID number of the camera concerned, and notifies the video reception software 412 of the ID of the dragged and dropped camera. On the basis of the notified ID, the video reception software 412 searches for the panning and tilting of the camera, the camera name and the name of the host

computer to which the camera is connected, and notifies the camera control client software 411 and the map management software 413 of such information.

5 The camera control client software 411 communicates with the camera control server software 421 of the video transmitter 20 to which the video camera 10 is connected, through the network 100 in accordance with the notified information. Hereafter, the operation of the video camera 10 connected to the video transmitter 20 is controlled between the camera control client software 411 of the monitor 60 and the camera control server software 421 of the video transmitter 20 concerned. The information concerning the panning operation, the
10 tilting operation and the like of the camera (i.e., the information concerning the camera state) is notified from the camera control client software 411 to the video reception software 412 for a predetermined time or for each issuance of a camera control command.

 The map management software 413 updates the map stored in the video
15 board 136, thereby changing the direction of the camera icon according to the direction of the actual video camera 10, drawing a scope 910 (Fig. 9) representing that the video (or the image) taken by the video camera 10 concerned is being displayed, and drawing a control pointer 920 (Fig. 9) within the scope 910 to control the panning, tilting and zooming operations of the camera.

20 Further, the information concerning the panning operation, the tilting operation and the like of the camera is notified from the video reception software 412 to the map management software 413 for a predetermined time or for each issuance of a the camera control command. Thus, if the panning state, the tilting state, the zooming state and the like of the camera are changed on the camera

control panel 640, such a the change is reflected on the displaying states of the camera icons 521, 522, 523, 524 and the like.

If the camera control server software 421 starts, it communicates with the map management server software 431 through the network 100. Hereafter, if ~~the~~
5 connection is requested from the camera control client software 411, the camera control server software 421 performs predetermined connection processing.

If ~~the~~ video display processing starts and a the connection between the camera control server software 421 and the camera control client software 411 is established, the camera control server software 421 notifies the map management
10 server software of such a fact.

Hereafter, until the camera control server software 421 is disconnected from the camera control client software 411, the camera control server software 421 notifies the map management server software of "camera state information" every time the state of the video camera is changed or every time a certain time
15 period, initially set by the camera control server software 421, ~~421~~ elapses.

The camera state information includes a time (i.e., a time stamp) when the information is transmitted, attributes of the video camera (i.e., a panning value, a tilting value, a zooming value, etc.), the connection state to the camera control client software 411, a network address of the connected monitor terminal in which
20 the camera control client software 411 is located, and the like.

The map management server software 431 unitarily manages the camera state information transmitted from the entire video camera control server software 421 running within the system.

Every time new camera state information is notified from ~~a~~ the camera control server software, or every time a certain time period initially set elapses, the map management server software 431 notifies all the monitors 60 running within the system of the camera state information of all the connected video transmitters

5 20. The network address of the monitor 60 is notified to the map management server software 431 when the video reception software 412 starts operation. Also, the network address may be fixedly set in the map management server software 431 or may be obtained based on the camera state information.

The camera state information is actually received by the video reception

10 software 412 and shared by the camera control client software 411 and the map management software 413.

The camera state information from the map management server software 431 is notified to the video reception software 412. Further, the information sent from the camera control client software 411 of the monitor 60 as a result of ~~a~~ the

15 camera controlling operation is notified to the video reception software 412.

In order to correctly manage ~~this~~ these information timewise, the camera state information is time-stamp managed for each video camera in this system.

When the camera state information is notified by the video reception software 412, the time stamp of each camera is compared with the previous information. If the

20 time stamp is newer than the previous one, the time stamp is updated, while if the time stamp is older than the previous one, the time stamp is discarded.

After the camera state information is updated as above, the video reception software 412 notifies the map management software 413 of such a fact.

The map management software 413 changes and updates the camera symbol on the

map on the basis of that information. In this case, the change of the display represents changes of photographing range and zooming (i.e., the area 580) shown in Fig. 6.

In Fig. 2, the map management server software 431 is illustrated to be
5 executed in ~~a the~~ specific video transmitter 20. However, the map management server software 431 may be executed in any ~~of an~~ arbitrary video transmitter, an arbitrary monitor or another computer connected to the ~~identical~~ network.

The actual image data is transmitted from the video transmitter 20 in accordance with the request from the video reception software 412 of the monitor
10 60. The video reception software 412 transmits a command to the video transmission software 422 of the video transmitter 20 to which the video camera 10 concerned is connected, through the network 100. This command is to request data transmission of one frame. The video transmission software 422 receives the command, divides the captured latest frame data into packets, and then transmits
15 these packets to the video reception software 412. The video reception software 412 reconstructs ~~restructures~~ the image frame from the received packets, displays the reconstructed ~~restructured~~ image frame on the video display area, and again transmits ~~a the~~ video transmission request command. By repeating such operations at high speed, ~~the~~ video taken at ~~a the~~ remote location is transmitted and displayed
20 through the network 100. Thus, ~~the~~ video taken by a remote ~~the~~ video camera 10 ~~remotely located~~ is displayed on the bit map display 135 of a local ~~the~~ monitor 60.

When ~~the~~ videos taken by the plural video cameras 10 are displayed on plural ~~the~~ screens, ~~a the~~ video transmission request command is issued, ~~a the~~ captured video is compressed, ~~a the~~ frame is divided into ~~the~~ packets, the divided

packets are transmitted to the network, the packets are received, the frame is reconstructed ~~restructured~~, the compressed data is decompressed, and the decompressed video data is displayed in turn and repeatedly, for ~~each of~~ the video transmission software of the respective video transmitter 20 to which each camera
5 is connected.

The video taken by the video camera can be shifted by dragging and dropping the displayed video to the desired video display area, ~~area~~ as shown in Fig. 8. Fig. 8 shows the state that ~~the~~ video taken by the video camera icon 523 and displayed on the video display area 614 is shifted to the video display area 612.
10 At this time, the video reception software 412 clears the area 614, and changes internal parameters such that the area 612 (i.e., the drag-and-drop destination) acts as the video display area of the video of the camera 10. Hereafter, ~~the~~ video taken by the video camera 10 concerned is displayed on the drag-and-drop destination. It should be noted that the logical network is not disconnected even by such ~~the~~
15 operation. Namely, as described later, the once-connected communication network is not disconnected until the video display area displaying the video is dragged and dropped into the trash can icon.

The display of ~~the~~ video taken by the video camera 10 is stopped as shown in Fig. 10. Namely, the video display area on which the video intended to
20 be deleted is being displayed is dragged and dropped into the trash can icon 632 within the video display window. Fig. 10 shows the state after the display of the video of the video camera icon 523 on the video display area 614 is stopped. At this time, the video reception software 412 clears the area 614 to stop issuing the video transmission request command to the software 412 of the video transmitter

20 connected till then. Further, the video reception software 412 notifies the camera control client software 411 and the map management software 413 of the fact that the display was stopped.

The camera control client software 411 receives such ~~the~~ notification,
5 disconnects ~~the network to~~ the video transmitter 20 concerned from the network, and clears the corresponding video display area. Further, the map management software 413 eliminates the scope display from the icon 523 of the video camera concerned, and updates the map.

Figs. 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29,
10 30, 31, 32, 33, 34, 35, 36, 37 and 38 are flow charts showing the above-explained software processing.

Hereinafter, the respective steps in the flow charts will be explained.

In the flow charts, it should be noted that a ~~the~~ step boxed by dotted lines represents the processing by which some communications are performed to another
15 software.

One software is executed in parallel with another software by the function of an operating system (OS). Further, there is a possibility that CPU resources are allocated to another software while one software is being executed.

20 (Map Management Software: Figs. 12 and 13)

In steps S100 and S102, the map management software 413 shown in Fig. 2 starts operation, and, for example, the map window 500 shown in Fig. 3 is displayed on the bit map display 135.

Steps S110, S112 and S114 represent ~~the~~ processing when ~~that~~ the camera symbol (e.g., the video camera icon 521 of Fig. 3) on the window 500 is clicked.

If the video of the video camera represented by this camera symbol has been displayed on the video window (e.g., the video display area 610 of Fig. 5), the map

5 management software 413 notifies the video reception software of focus change (i.e., change of the target to be controlled). This processing will be explained later in ~~in a~~ step S285.

Steps S120, S122, S124, S125 and S126 represent ~~the~~ processing when ~~that~~ the camera symbol (e.g., the video camera icon 521 of Fig. 3) on the map

10 window is dragged. While the symbol is being dragged, the shape of the mouse cursor is changed, ~~changed~~ as shown in Fig. 7. Then, ~~Then~~ the shape of the mouse cursor is restored when if the cursor is dropped.

When If the mouse cursor is dropped into a ~~the~~ video window, the map management software 413 notifies the video reception software of the drop

15 operation. This processing will be explained later in a step S260.

In steps S130 and S132, when if the map tab of a ~~the~~ map (e.g., the map 510, 520 or 530 of Fig. 6) is clicked, the map is changed to the map having the clicked map tab, and the display of the map and the camera symbols is updated.

Steps S140, S150 and S152 represent ~~the~~ processing which is performed

20 when a ~~the~~ focus change (i.e., a ~~the~~ change of the target to be controlled) is notified from the video reception software by clicking the video on the video window in later-described steps S234, S256 and S267.

Then, ~~Then~~ the map is changed such that a ~~the~~ camera symbol corresponding to a ~~the~~ focused video is displayed at the center of the map window, and the camera symbol is displayed.

If a ~~the~~ camera state is notified from the video reception software in
5 later-described steps S257, S268, S296 and S314, the state display of the camera symbol is updated according to the camera state information.

In steps S160, S162 and S172, when if the end menu on the map window displayed by a predetermined operation is clicked, the map management software 413 notifies the video reception software of the end, and the map management
10 software ends.

Steps S180, S182 and S184 represent ~~the~~ processing which is performed when the video camera is controlled by dragging the map symbol (e.g., the control pointer 920 of Fig. 9) with the mouse. The map management software 413 updates the display state of the camera symbol concerned, and notifies the video reception
15 software to control the corresponding video camera.

(Video Reception Software: Figs. 14 to 20)

In step ~~a-step~~ S200, the video reception software 412 starts operation, and the video window (i.e., the window 600) is displayed on the bit map display 135.

20 In steps S210, S212 and S214, the video reception software 412 is connected to the predetermined map management server software and starts communication. In this case, an internal flag is set to ON ~~on~~ if the video reception software 412 succeeds in connecting with the map management server software,

while the internal flag is set to OFF off if the video reception software 412 fails to make a connection in.

In steps S220, S222, S224, S226 and S228, if the map management software 413 ends due to the ~~by the~~ processing in ~~the~~ steps S160, S162 and S172,
5 the video reception software 412 stops displaying the video and disconnects the video transmission software. ~~Then,~~ Then the map management software 413 notifies the camera control client software to disconnect the camera control server software, and the video reception software ends.

In steps S230, S232 and S234, if the displayed video (e.g., the video of the
10 display area 614 of Fig. 6) is clicked, the focus (the target to be controlled) is changed to the clicked video, and the video reception software 412 notifies the map management software and the camera control client software of focus change (i.e., change of the target to be controlled). Therefore, the map management software performs the processing in ~~the~~ step S140, and the camera control client software
15 performs the processing in ~~the~~ step S420 (see below).

Steps S240, S241, S242, S244, S246, S247, S248, S250, S251, S252, S253, S254, S255, S256, S257, S258 and S259 represent ~~the~~ processing which is performed when the displayed video (e.g., the video of the display area 614 of Fig. 8) is dragged to the display area 612, or when the displayed video (i.e., the video of
20 the display area 614 of Fig. 10) is dragged to the display area 632 (trash can).

If the video is dropped into the trash can icon, the display of the dropped video is stopped, and ~~the~~ communication with the camera from which the video was being is transmitted ends (Fig. 15). If the video is dropped into another video display window in which ~~there is~~ no video is being displayed, the video is shifted

to this video display window (i.e., the drop destination window) ~~destination~~
~~window~~. On the other hand, if there is a the video being displayed in this drop
destination window, ~~the~~ communication with the camera which transmits the video
to this drop destination window ends, and the dragged/dropped video display is
5 shifted to this video display window (i.e., the drop destination window; see
destination) window (Fig. 16).

Steps S260, S261, S262, S263, S264, S265, S266, S267 and S268
represent ~~the~~ processing which is performed when, e.g., ~~the~~ video camera icon 523
is dropped into the video display area 614, ~~614~~ as shown in Fig. 6.

10 If there is ~~the~~ video being displayed in the display area of the drop
destination, ~~the~~ communication with the video camera which transmits this video
ends. Thus, the video which is transmitted from the terminal corresponding to the
video camera icon 523 is displayed in the display area of the drop destination (Fig.
17).

15 Steps S270 and S272 represent ~~the~~ processing which is performed when
the video information is updated in the case where video is being there is the
displayed ~~video~~, after the processing in ~~the~~ steps S260 to S268. In this the
processing, ~~the~~ video is requested to the video transmission software at
predetermined timing. Then, ~~Then~~ the video transmission software performs the
20 processing in accordance with ~~corresponding to~~ a later-described S530.

Steps S275 and 8276 represent ~~the~~ processing which is performed when
the video information is transmitted from the video transmission software.

Steps S280 and S282 represent ~~the~~ processing which is performed when the camera symbol on the map management software is mouse-operated (steps ~~step~~ S180 to S184).

5 The video reception software notifies the camera control client software to control the video camera which is currently being focused (i.e., ~~being~~ the target to be controlled). Thus, ~~Thus~~ the camera control client software performs the corresponding processing in a later-described step S430.

Steps S285, S286 and S287 represent ~~the~~ processing which is performed when the camera symbol on the map management software is clicked by the mouse
10 (steps S110 to S114).

The video reception software notifies the camera control client software to change the focus (i.e., the target to be controlled) of the camera corresponding to the camera symbol. Thus, ~~Thus~~ the camera control client software performs the processing in a later-described step S420.

15 Steps S290, S292, S294, S295 and S296 represent ~~the~~ processing which is performed when the camera state is notified from the map management software or the camera control client software.

The camera state information of the overall ~~entire~~ camera control server software connected is transmitted from the map management server software, at a
20 ~~the~~ timing when the new information is transmitted from the camera control server software and the camera state information is updated.

A camera control instruction is transmitted from the camera control client software to the camera control server software every time the video camera is controlled.

The camera state information transmitted to the video reception software is subjected to old and new judgment ~~by~~ using the time stamp for each video camera. The camera state information is updated if it is new, while the camera state information is discarded if it is old.

- 5 The updated camera state information is notified to the map management software and processed in ~~the~~ step S150.

In ~~step a-step~~ S300, if the connected video transmission software ends due to ~~by~~ the processing of later-described steps S510 to S514, the video transmission software concerned is disconnected.

- 10 In steps S310, S312 and S314, if the camera control server software to which the camera control client software is connected ends due to ~~by~~ the processing of later-described steps S410 to S412, the video transmission software of the video transmitter 20 to which the camera control server software is connected is disconnected.

- 15 In steps S315 and S316, if the connected map management server software ends, the connection flag to the map management server software is turned OFF ~~off~~, and the map management server software is disconnected.

- In ~~step a-step~~ S320, the connection flag to the map management server software is checked, and reconnection processing is performed if the map
20 management server software is not connected.

This ~~is the processing prevents which is to prevent~~ restart of the entire system when the map management server software is temporarily stopped for some reasons and then restarted.

(Camera Control Client Software: Figs. 21 and 22)

In ~~step a-step~~ S400, the camera control client software 411 starts operation, and the camera control window (e.g., the video camera control panel 640) is displayed on the bit map display 135.

5 In steps S410 and S412, if the video reception software ends due to ~~by~~ the processing in ~~the~~ steps S220 to S228, or if the camera control server software ends due to ~~by~~ the processing in ~~the~~ steps S620 to S622, the camera control client software disconnects the camera control server software, whereby the camera control client software ends.

10 In steps S420 and S422, if ~~a the~~ focus change is notified by the processing in ~~the~~ steps S234, S267 and S287, the camera control client software checks whether or not the focused video camera is currently controllable (accessible). If controllable, for example, the control button on the video camera control panel 640 is made available.

15 In steps S430, S432 and S435, if the camera control is notified from the video reception software in ~~the~~ step S282, or if the control button is clicked, the camera control client software transmits the control command to the focused camera.

Steps S440 and S442 represent ~~the~~ processing which is performed when
20 the camera control server software returns to the video reception software ~~the~~ notification that ~~a the~~ control command from the camera control server software was received in ~~step a-step~~ S642, by the processing in ~~the~~ steps S430 to S435. Namely, the camera state is notified to the video reception software. The video reception software processes the returned notification in ~~the~~ step S295.

In steps S450, S452 and S454, the video reception software connects to the camera control client software corresponding to the camera symbol into which the video is dropped, in response to the notification in the step S266. After the connection, the camera control client software notifies the video reception software of the camera state. The video reception software processes this notification in the step S295.

In steps S460, S462 and S464, the camera control client software disconnects the focused camera control server software on the basis of the disconnection notification in the steps S248, S254 and S264. After the disconnection, the camera state is notified to the video reception software. The video reception software processes this notification in the step S295.

(Video Transmission Software: Fig. 23)

Steps S500, S510, S512, S514, S520, S522, S530, S532, S540 and S542 represent the operation of the video transmission software.

Further, these steps represent in detail the processing flows of the video reception client software, the video reception software and the video display software.

(Camera Control Server Software: Figs. 24 and 25)

In ~~step a step~~ S600, the camera control server software starts operation.

In steps S610, S612 and S615, the camera control server software connects to the predetermined map management server software and starts the communication. In this case, an internal flag is set to ON ~~on~~ if the camera control

server software succeeds in connecting with the map management server software, while the internal flag is set to OFF off if the camera control server software 412 fails to make a connection in.

Steps S620, S622 and S624 represent ~~the~~ processing which is performed
5 when the end menu is clicked by ~~a the~~ predetermined operation.

The camera control server software notifies the map management server software, ~~software~~ and the camera control client software in connection, of the end. Then the camera control server software ends.

Steps S630 and S632 represent ~~the~~ processing which is performed when
10 the camera control client software performs the connection processing in ~~the~~ step S452.

Steps S640, S642, S644 and S646 represent ~~the~~ processing which is performed when ~~a the~~ control instruction is issued from the camera control client software in ~~the~~ step S432. In this case, the video ~~vide~~ camera is controlled, and
15 thus obtained camera information is notified to the camera control client software.

If the connection to the map management server software has been established, the camera state information is notified also to the map management server software.

Steps S650 and S652 represent ~~the~~ processing which is performed when
20 the disconnection processing is performed by the camera control client software in ~~the~~ step S462.

Step S660 and S662 represent ~~the~~ processing which is performed when the map management server software ends in later-described steps S710 to S714.

In this case, the connection ends, and the connection flag is turned OFF off.

In ~~step a-step~~ S670, the connection flag to the map management server software is checked, and reconnection processing is performed if the map
5 management server software is not connected.

This ~~is the~~ processing prevents ~~which is to prevent~~ restart of the entire system when the map management server software is temporarily stopped for some reasons and then restarted.

10 (Map Management Server Software: Figs. 26 and 27)

In ~~step a-step~~ S700, the map management server software starts operation.

In steps S710, S712 and S714, when if the displayed end menu is clicked by a ~~the~~ predetermined operation, the map management server software notifies the camera control server software, ~~software~~ and the video reception software in
15 connection, of the end. Then the map management server software ends.

In steps S720, S722, S730 and S732, processing it waits for a ~~the~~ connection request from the camera control server software and the video reception software. If the request is transmitted, the corresponding connection processing is performed.

20 Steps S750, S752, S760 and S762 represent ~~the~~ processing which is performed when ~~the~~ disconnection requests are transmitted from the camera control server software and the video reception software. In this case, the corresponding disconnection processing is performed.

[Second Embodiment: Figs. 28 and 29]

In the first embodiment, the camera state is notified to the video reception software at a the timing when the camera state is notified from the camera control server software. However, in the second embodiment, the camera state is notified
5 to the video reception software after a predetermined time period elapses.

Figs. 28 and 29 are ~~shows the~~ flow charts showing the operation of the map management server software. It should be noted that the operations of other software in the second embodiment are substantially the same as those in the first embodiment.

10 The changed parts (i.e., ~~the~~ parts different from those of the first embodiment) in the flow charts are as follows.

In steps S740 and S742, if the camera state is notified from the camera control server software, the camera information of the video camera concerned is updated.

15 In steps S770 and S772, when if the previously set (predetermined) time period elapses, the camera information of all the video cameras is notified to the video reception software of the plural monitors in connection.

[Third Embodiment: Figs. 30, 31 and 32]

20 In the first embodiment, the map management server software notifies the camera state to the video reception software. However, in the third embodiment, the video reception software inquires of the map management server software as to the camera state every time a predetermined time period elapses.

Fig. 30 shows the operation flow of the third embodiment which is different from that of the first embodiment.

The changed parts (i.e., ~~the~~ parts different from those of the first embodiment) in the flow charts are as follows. It should be noted that the
5 operations of other software in the third embodiment are substantially the same as those in the first embodiment.

In steps S290 and S291, instead of the processing in which ~~that~~ the camera state notification is checked from the map management server software, a
~~the~~ map state request is notified to the map management server software every time
10 a the predetermined time period elapses, and the video reception software waits until the camera state is notified. It should be noted that the processing after the camera state is notified is the same as that in the first embodiment.

Figs. 31 and 32 show the operation flow of the map management server software.

15 The changed parts (i.e., ~~the~~ parts different from those of the first embodiment) in the flow charts are as follows. It should be noted that the operations of other software in the third embodiment are substantially the same as those in the first embodiment.

In steps S740 and S742, if the camera state is notified from the camera
20 control server software, the camera information of the video camera concerned is updated. At this timing, the camera state is not notified to the video reception software in connection.

In steps S770 and S772, if a the camera state request is notified from the video reception software, the camera state is notified to the video reception

software concerned. Unlike the first embodiment, such ~~the~~ camera state is not notified simultaneously to all the video reception terminals connected to the map management server software.

5 [Fourth Embodiment: Figs. 33, 34 and 35]

In the first to third embodiments, the file which represents the structure of the map itself is called a "map file", ~~file~~ in which ~~the~~ bit map images, ~~images~~ such as the map and the camera symbols, the locations of the camera symbols on the map, the kinds of video cameras and the like have been written, ~~written~~ is held in
10 each map management software.

However, in the fourth embodiment, the map management server software unitarily manages the map file.

In By the fourth embodiment, in addition to the camera state when the system is operating, the bit map images of the map and the camera symbols, the
15 locations of the camera symbols on the map are unitarily managed. Thus, the user can use the identical map at all ~~the~~ monitors accessing the identical map management server software.

In the present embodiment, a communication capability to the map management server software is added to the map management software in the first
20 embodiment, whereby the map management software of the monitor 60 can obtain the bit map images of the map and the camera symbols from the map management server software of the video monitor 20.

The changed parts (i.e., ~~the~~ parts different from those of the first embodiment) in the flow charts are shown in Figs. 34 and 35. It should be noted

that the operations of other software in the fourth embodiment are substantially the same as those in the first embodiment on the premise that "camera information" (i.e., the camera information of all the video cameras) is replaced with "map file information" (i.e., ~~the~~ bit map images such as the map and the camera symbols, the
5 locations
of the camera symbols on the map, the kinds of video cameras, and the camera information of all the video cameras).

However, if the bit map file is frequently copied, ~~a the~~ load is placed on
~~given to~~ the processing. Therefore, the bit map file may be copied only at a the
10 timing when the map management software starts and when an update button 590
of Fig. 11 is clicked by the mouse.

In ~~step a step~~ S102, if the map management software starts, it connects to the map management server software and requests a the map file (i.e., ~~the~~ bit map images such as the map and the camera symbols, the locations of the camera
15 symbols on the map, the kinds of video cameras, and the camera information of all the video cameras). Then the map management software receives the data, and displays the map and the camera symbols on the window in accordance with the received data.

In steps S190 and S192, when the update button is clicked, the map
20 management software connects to the map management server software, requests a the map file (i.e., ~~the~~ bit map images such as the map and the camera symbols, the locations of the camera symbols on the map, the kinds of video cameras, and the camera information of all the video cameras), and receives the data. Then the map

management software displays the map and the camera symbols on the window in accordance with the received data.

By the above processing, in the case where ~~the~~ bit map images such as the map and the camera symbols, and the locations of the camera symbols on the map are changed while the map management software is running, it is possible to obtain
5 the data after the change without restarting the system.

In steps S770 and 772, if ~~a the~~ map file is requested from the map management software, the map file is transmitted, and the map management software is disconnected.

10 By the above procedure, ~~a the~~ map file can be always maintained and updated unitarily, whereby the user can use the identical map at all ~~the~~ monitors accessing the identical map management server software. Also, the new camera information can be always displayed.

In this case, although the present embodiment has been explained in the
15 form of expansion of the system already explained in the first embodiment, the present embodiment is not limited to this.

For example, the map management server software may be replaced with Web server software, the map management software may be replaced with Web browser software, and the video display client software or the camera control client
20 software may be replaced with plug-in software or helper application.

In this case, ~~a the~~ map file may be obtained from the Web server software every time an update button on Netscape Navigator or Internet Explorer is clicked, as shown in the third embodiment.

Further, by using a so-called server push method which transmits the data from the Web server software to the Web browser software without request from the Web browser, ~~a~~ the map file transmitted as in the first and second embodiments may be received.

5

[Fifth Embodiment: Figs. 36, 37 and 38]

In the fourth embodiment, ~~the~~ bit map images such as the map and the camera symbols and the locations of the camera symbols on the map are unitarily managed by the map management server software.

10

When the actual camera disposing location and the initial direction of a pan head are changed, it is necessary to update the map file according to the change. However, the video camera is not always disposed at the location in the vicinity of the map management server software; if so, the user must move to the location of the map management server software and change the map file after the
15 actual camera disposing location is changed. It seriously increases costs to do so, so both in time and operation.

The fifth embodiment is directed to one example to solve such a problem. In the present embodiment, coordinates of the camera symbol on the map corresponding to the video camera concerned and an input unit for inputting the
20 initial direction of the pan head are provided for the camera control server software. Further, ~~the~~ a communication unit for communicating the input information to the camera management server software is also provided.

The changed parts (i.e., ~~the~~ parts different from those of the first embodiment) in the flow charts are shown in Figs. 36 to 38.

In ~~step a-step~~ S602, when if the camera control server software starts, the coordinates of the camera symbol on the map connected to the video transmitter in which the camera control server software concerned is running and the initial direction of the pan head are read from the predetermined initial setting file.

- 5 In ~~step a-step~~ S612, if the connection to the map management server software ends, the coordinates of the video camera on the map and the initial direction of the pan head are notified to the map management server software.

The map management server software receives the data and updates the map file.

- 10 In ~~step a-step~~ S724, if the connection to the camera control server software ends, the map file is updated according to the notified coordinates of the video camera on the map and the notified initial direction of the pan head.

Step A-step S754 represents the processing which is performed when the camera control server software ends and the disconnection is notified.

- 15 The disconnection processing is performed, the map file is updated, and the fact that the camera control server software is ~~does not~~ running ~~run~~ is notified to the video reception software.

The video reception software notifies the map management software of such ~~the~~ information, and the map management software updates the map symbol.

20

[Other Embodiments]

The present invention is applicable to a system composed of plural pieces of equipment ~~equipments~~ (e.g., a host computer, ~~an~~ interface equipment, a reader, a

printer and the like) or to an apparatus including only a single piece of equipment (e.g., a copying machine, a facsimile machine or the like).

~~Needless It is needless to say, an that the~~ object of the present invention can be achieved in a case where a storage medium storing the program codes of of
5 a software for realizing the functions of the above-described embodiments is supplied to a system or an apparatus, ~~apparatus~~ and then a computer (or CPU or MPU) in the system or the apparatus reads and executes the program codes stored in the memory medium.

In this case the program codes themselves read from the storage medium
10 realize the functions of the embodiments, and the storage medium storing such ~~the~~ program codes constitutes ~~constitute~~ the present invention.

The storage medium storing the program codes can be, for example, a floppy disk, a hard disk, an optical disk, a magnetooptical disk, a CD-ROM, a CD-R, a magnetic tape, a non-volatile memory card, a ROM, or the like.

15 ~~The It is needless to say that the~~ present invention also includes not only the case where the functions of the embodiments are realized by the execution of the program codes read by the computer, but also a case where an OS (operating system) or the like functioning on the computer executes all the process or a part thereof according to the instructions of the program codes, thereby realizing the
20 functions of the embodiments.

~~The Further, it is needless to say that the~~ present invention further includes a case where the program codes read from the storage medium are first ~~once~~ stored in a memory provided in a function expansion board inserted into in the computer or a function expansion unit connected to the computer, and a CPU

or the like provided in the function expansion board or the function expansion unit executes all the process or a part thereof according to the instructions of such program codes, thereby realizing the functions of the embodiments.

According to the above-explained embodiments, the information of the
5 video camera and the map information in the vicinity of the location at which the video camera is disposed can be unitarily managed, and the managed information can be notified to all the terminals operating the video cameras timewise as accurately accurate as possible.

Further, in the communication apparatus which is connected to at least
10 one camera and at least one monitor and manages ~~the~~ information concerning the state of the camera, there are provided ~~the~~ reception means for receiving the information concerning the state of the camera, and ~~the~~ transmission means for transmitting the information concerning the state of the camera received by the reception means to the monitor, so as to change a display concerning the state of
15 the camera displayed on the monitor, whereby the state of the camera can be recognized at the monitor.

Further, when the image data taken by the camera is received by the monitor, the states of the camera (i.e., the disposing location, the photographing range, the information of zooming) can be simultaneously grasped.

20 Further, if ~~the~~ information concerning the state of the camera is transmitted according to the change of the state of the camera, the state of the camera can be quickly grasped. Further, since such ~~the~~ transmission is performed according to a ~~the~~ request from the monitor, the state of the camera can be grasped as necessary ~~according to necessity~~, without redundant transmission.

Further, in a ~~the~~ communication apparatus which is connected to at least one camera and at least one monitor and manages ~~the~~ information concerning the state of the camera, there are provided ~~the~~ reception means for receiving the information concerning the state of the camera, ~~the~~ processing means for changing
5 a ~~the~~ display image concerning the state of the camera displayed on the monitor, in accordance with ~~the~~ received information concerning the state of the camera, and ~~the~~ transmission means for transmitting the display image concerning the state of the camera processed by the processing means, to the monitor, whereby the display image concerning the state of the camera can be obtained at the monitor.

10 Therefore, if ~~the~~ information concerning the state of the camera is received at the monitor and a ~~the~~ display image is formed according to the received result, it is possible to prevent a need that the size of the monitor be increased ~~increases~~.

As a result, for example, as the number of the monitors increases, it is possible to reduce the size of the overall ~~entire~~ apparatus in the system including
15 the cameras, the communication units and the monitors.

Further, since ~~the~~ transmission is performed according to a ~~the~~ request from the monitor, it is possible to limit the number of transmissions ~~transmission~~ of ~~the~~ data (i.e., the image) of which data quantity is large.

Further, ~~the~~ transmission means is provided which transmits the
20 information concerning the state of the camera to the monitor such that the information concerning the state of the camera is reflected on the map screen for controlling the camera displayed on the monitor. Thus, even if the camera is distant from the monitor, the state of the camera can be quickly reflected on the monitor. For this reason, for example, if ~~the~~ plural cameras are provided ~~disposed~~,

the load to the operator can be reduced as compared with the case where the operator sets the state information of the plural cameras after he sets the plural cameras. Thus, it is possible to prevent an ~~the~~ error in which ~~that~~ the state of the camera does not coincide with that of the monitor.

ABSTRACT OF THE DISCLOSURE

In a system wherein one or more controllable camera(s) ~~camera~~ and one or
of more monitor(s) ~~monitor~~ for displaying video information received from the
camera(s) ~~camera~~ are connected to each other through a communication device, the
5 states of all the cameras can be always understood at any monitor. Map ~~Therefore,~~
~~map~~ management server software is provided to receive notification(s)
~~notifications~~ of camera state information by all the cameras with the predetermined
device, and to transmit the camera state information to all the monitors.

10 CPWgmc

DC_MAIN 165426v1